



DRIP HOSE BOOMS

9 TO 21 m



Precision, Productivity, Performance.



Precise spreading onto soil surface
Standard and telescopic models
High spreading output rates

DRIP HOSE BOOMS - 9 to 21 m

For precise spreading on growing crops

The advantages of our drip hose boom

- ✓ Fully galvanised structure
- ✓ Respect of soil structure
- ✓ Spreading on growing crops
- ✓ Reduced nitrogen loss
- ✓ Maximum value out of organic fertiliser
- ✓ Minimum smell
- ✓ Even transverse distribution
- ✓ Uniform volume spread on soil surface

Boom functions

In-cab simplified controls for:

- Boom arms opening/closing
- Hoses folding/unfolding (*no leaks during transport*)
- Telescopic function opening/closing (*if option*)
- Hydraulic locking

Advice for best use

The hose ends must touch the ground at all times when spreading.

- Higher value out for fertiliser
- Reduce nitrogen loss
- Low contamination of crops



Vertical Macerator(s)

- Ideal for spreading thick slurry
- Foreign bodies caught in the stone trap
- Optimise distribution of slurry
- Even outlet distribution



Half-width section cut-off (option)

- Feeding of right or left side of the boom
- Facilitate end of spreading operations
- Prevent overlapping
- Maximum spreading accuracy



Part-width section cut-off(s) (option)

- Air or manual operated
- Synchronised or unsynchronised right and left cut-off(s) of the boom sections
- Control in tractor's cab
- Easier to spread on headlands
- Maximum spreading accuracy



Active slope compensation (option)

- Boom always parallel to the ground
- Perfect distribution across the entire working width
- Reduced load on the boom structure

Features

Working width	Number of outlets	Hose diameter	Number of macerator(s)	Space between hoses
9	30	Ø40/50	1	33 cm
12	40	Ø40/50	1	30 cm
12/15	48	Ø40/50	2	31 cm
15	48	Ø40/50	1	31 cm
15/18	48	Ø40/50	2	37.5 cm
15/18	60	Ø40	2	30 cm
18	48	Ø50	1	37.5 cm
18	60	Ø40	2	30 cm
18/21	60	Ø40	2	35 cm

