



SV16





THE POWER OF A SCALABLE MACHINE

SV16

ANTICIPATING THE FUTURE

- Predefined tank
- Compatible, built-in frame for undercarriage & tandem
- Low centre of gravity = Ensured stability
- Optimised maximum GVW (28 tons)
- Equipment adapted to your spreading implements
 - EL61 tine incorporator - 3 to 6 m in width
 - Trailing shoe - 9 to 15 m in width
 - Drip hose booms - 9 to 15 m in width

ICONTROL7S: NEW CONTROL SYSTEM

- Optimised touch surface (7" screen)
- Improved ergonomics and updated interface
- Simplified terminal setup
- Efficient machine steering and control
- Automated work cycles
- Real-time feedback on the screen
- Tracking and recording of operations carried out



BRACKETS ON TANK

- 2 SV16BP and SV16BT tank models
- Universal undercarriage/tandem frame
- Brackets for 4-point linkage
- Brackets for add. unloading pipe



UNLOADING PIPE

- Ø200 inner/upper pipe
- Stone trap
- Brackets for hyd. turbo feeder
- Brackets for flowmeter



BOGIE

- New parabolic spring suspension
- Extensive articulation
- Heavy-duty mounting
- Axle wheelbase > 1.80 m



USER ACCESSORIES

- Toolbox
- Hand-wash basin with soap basin
- Pipe storage tray

Features	SV16
Length	9 000 mm
Tank diameter	1 800 mm
Max. height	4 100 mm
Width incl. wheels 600/55R26.5	2 850 mm
Width incl. wheels 650/65R26.5	2 900 mm
Track	2 150 mm
Min./max. tare weight excl. devices	8.0 t / 10.5 t
Target volume	16 600 L