



SV15R





THE PERFECT COMBINATION OF POWER AND TRACTION

SV15R

- Integrated chassis and low centre of gravity due to recessed wheels
- Filling system and vacuum unloading as standard
- High-quality interior and exterior treatment
- Optimised maximum GVW (28 tonnes)
- Flexible filling solutions: BP2, plunger and turret
- External filling with a Ø400 mm opening
- Scalable unloading pipe to complete the most demanding application tasks (flow regulation, turbo filler, etc.)
- Flexible application solutions: drip hoses, incorporators and injectors



RECESSED WHEELS

- No tank volume reduction
- Steering angle up to 12°
- Adapted for Ø1650 mm wheels
- Low rolling resistance
- Less power consumed



WEIGHT TRANSFER SYSTEM *(option)*

- Excellent adhesion until the end of unloading
- Prevents load-shedding on tractor coupling
- Automatic unloading of compartment no. 2



DRIVE WITH COMPLETE PEACE OF MIND

- Tandem with reinforced swivel pins
- Optimised section for improved resistance
- Dimensions for a 15 t load per axle



iControl 7S TERMINAL

- Manual joystick with 7-inch touchscreen
- Automated work cycles
- Dosage adjustment
- Data tracking and saving

Specifications	SV15R
Length	9100 mm
Tank diameter	1800 mm
Max. height	4000 mm
Width incl. 650/65R30.5 tyres	2980 mm
Width incl. 750/60R30.5 tyres	3000 mm
Track	2200 mm
Min./max. tare weight excl. devices	8.5 t/10.0 t
Target volume	15.6 m ³